

View Online at <https://aerobasegroup.com/nsn/5930-00-548-7945>

**Overall Height:**

6.750 inches

**Overall Width:**

6.750 inches

**First Flat Length:**

0.875 inches single actuator

**Flat Height:**

0.467 inches single actuator

**Shaft Diameter:**

0.625 inches single actuator

**Shaft Length:**

1.812 inches single actuator

**Unthreaded Mounting Hole Diameter:**

0.500 inches single mounting facility

**Individual Section Quantity:**

3

**Knob Manufacturer Code:**

80064

**Knob Manufacturer Part Number:**

9s5360pc6

**Longest Horizontal Distance Between Mounting Centers:**

5.625 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

5.625 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

2 each section front

**Features Provided:**

Actuator knob

**Contact Voltage Rating In Volts:**

500.0 ac at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Threaded stud

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Contact Load Current Rating:**

200.0 amperes resistive load ac at sea level

**Test Data Document:**

81349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Or Standard:**

20sr class

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0