## NSN 5930-00-548-7948

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-548-7948

Overall Length:
10.063 inches
Overall Height:
6.750 inches
Overall Width:
6.750 inches
First Flat Length:
0.875 inches single actuator
Flat Height:
0.467 inches single actuator
Shaft Diameter:
0.625 inches single actuator
Shaft Length:
1.188 inches single actuator
Unthreaded Mounting Hole Diameter:
0.500 inches single mounting facility
Individual Section Quantity:
4
Knob Manufacturer Code:
80064
Knob Manufacturer Part Number:
9s5360pc6
Longest Horizontal Distance Between Mounting Centers:
5.625 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
5.625 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
500.0 ac at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
4 single actuator
Shaft Type:
Round, flatted single actuator
Terminal Type:

Threaded stud

## **NSN 5930-00-548-7948**Rotary Switch - Page 2 of 2

Fiig: A052b0



Contact Switching Action:
Breaks before makes each section front
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Contact Load Current Rating:
200.0 amperes resistive load ac at sea level
Style Designator:
Tap, circuit selector
Test Data Document:
81349-mil-s-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Or Standard:
20sr class
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No