## NSN 5930-00-548-7958

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-548-7958

## Thread Length: 0.312 inches single mounting facility **Hazardous Locations/environmental Protection:** Watertight **Overall Length:** 2.671 inches **Overall Height:** 1.750 inches **Overall Width:** 1.016 inches First Flat Length: 0.438 inches single actuator Flat Height: 0.217 inches single actuator **Shaft Diameter:** 0.249 inches single actuator **Shaft Length:** 0.812 inches single actuator **Individual Section Quantity: Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 2 single section front **Throw Quantity:** 1 single section front **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 250.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 2 single actuator **Shaft Type:** Round, flatted single actuator **Terminal Type:** Tab w/screw **Contact Switching Action:** Breaks before makes single section front **Switch Actuator Positioning Increment:**

45.0 degrees single actuator

## NSN 5930-00-548-7958

Rotary Switch - Page 2 of 2



| Contact | Load | Current | Rating: |
|---------|------|---------|---------|
|---------|------|---------|---------|

3.0 amperes resistive load ac at sea level

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0