

View Online at <https://aerobasegroup.com/nsn/5930-00-548-7963>

Hazardous Locations/environmental Protection:

Watertight

Overall Height:

7.750 inches

Overall Width:

7.062 inches

First Flat Length:

0.875 inches single actuator

Flat Height:

0.467 inches single actuator

Shaft Diameter:

0.375 inches single actuator

Shaft Length:

1.750 inches single actuator

Unthreaded Mounting Hole Diameter:

0.531 inches single mounting facility

Individual Section Quantity:

5

Knob Manufacturer Code:

80064

Knob Manufacturer Part Number:

9000s6202-74388

Longest Horizontal Distance Between Mounting Centers:

6.500 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

7.625 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Mounting Method:

Base single mounting facility

Features Provided:

Actuator knob and metallic inclosure

Contact Voltage Rating In Volts:

125.0 ac at sea level

Mounting Facility Pattern:

Isosceles triangle single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Makes before breaks, breaks before makes each section front

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

25.0 amperes resistive load ac at sea level

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0