

<b>NSN 5930-00-548-7963</b> Rotary Switch - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5930-00-548-7963
Hazardous Locations/environmental Protection:
Watertight
Overall Height:
7.750 inches
Overall Width:
7.062 inches
First Flat Length:
0.875 inches single actuator
Flat Height:
0.467 inches single actuator
Shaft Diameter:
0.375 inches single actuator
Shaft Length:
1.750 inches single actuator
Unthreaded Mounting Hole Diameter:
0.531 inches single mounting facility
Individual Section Quantity:
5
Knob Manufacturer Code:
80064
Knob Manufacturer Part Number:
9000s6202-74388
Longest Horizontal Distance Between Mounting Centers:
6.500 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
7.625 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Mounting Method:
Base single mounting facility
Features Provided:
Actuator knob and metallic inclosure
Contact Voltage Rating In Volts:
125.0 ac at sea level
Mounting Facility Pattern:
Isosceles triangle single mounting facility
Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab w/screw

## NSN 5930-00-548-7963

Rotary Switch - Page 2 of 2



**Contact Switching Action:** 

Makes before breaks, breaks before makes each section front

**Switch Actuator Positioning Increment:** 

90.0 degrees single actuator

**Contact Load Current Rating:** 

25.0 amperes resistive load ac at sea level

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0