NSN 5930-00-548-7982

Lever Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-548-7982

Body Style:
Hole mounted
Overall Length:
4.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
Between 0.515 inches and 0.547 inches
Overall Width:
0.938 inches
Body Width:
Between 0.922 inches and 0.954 inches
Body Height:
Between 1.172 inches and 1.204 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 0.796 inches and 0.828 inches
Actuator Style:
Round
Actuator Diameter:
Between 0.265 inches and 0.297 inches
Actuator Height:
Between 1.218 inches and 1.250 inches
Actuator Position-action Relationship:
Up position momentary and down position maintained and center position maintained
Actuator Color:
Black single actuator
Maximum Voltage Rating In Volts:
110.0 ac
Inclosure Type:
Uninclosed
Mounting Method:
Unthreaded hole
Thready Qty Per Inch (tpi):
48
Pile-up Contact Form Arrangement:
2a 2nd position
Thread Size:
0.099 inches
Contact Load Current Rating At Maximum Rated Voltage:
3.000 amperes resistive ac
Thread Series Designator:
Unc

Terminal Type And Quantity:

8 tab, solder lug

NSN 5930-00-548-7982

Lever Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0