## NSN 5930-00-548-7983

Lever Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-548-7983

Body Style:
Hole mounted
Overall Length:
2.050 inches
Overall Height:
1.880 inches
Overall Width:
0.440 inches
Body Length:
Between 1.380 inches and 1.440 inches
Body Width:
Between 0.410 inches and 0.470 inches
Body Height:
Between 1.850 inches and 1.910 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.615 inches and 1.635 inches
Actuator Style:
Rectangular
Actuator Height:
Between 0.610 inches and 0.670 inches
Actuator Position-action Relationship:
Up position maintained and down position maintained and center position maintained
Actuator Position-locking Relationship:
Up position locked in and down position locked in and center position locked in
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Thready Qty Per Inch (tpi):
32
Pile-up Contact Form Arrangement:
1a 2nd position
Thread Size:
0.099 inches
Contact Load Current Rating At Maximum Rated Voltage:
1.500 amperes resistive dc and 230.000 milliamperes resistive ac
Special Features:

Terminals silver

**Precious Material And Location:** 

Switch supplied with two mounting screws and one knob, black

## NSN 5930-00-548-7983

Lever Switch - Page 2 of 2



Thread Series Designator:
Uns
<b>Terminal Type And Quantity</b>
4 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0