NSN 5930-00-548-8039

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-548-8039

Thread Class: 2a single mounting facility Thread Length: 0.375 inches single mounting facility **Overall Length:** 3.043 inches **Overall Height:** 1.500 inches **Overall Width:** 1.313 inches **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 1.875 inches single actuator **Nonturn Device Radius:** 0.438 inches at 9: 00 o'clock **Individual Section Quantity:** 1 **Nonturn Device Type:** Tab at 9: 00 o'clock **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 2 single section front **Throw Quantity:** 5 single section rear **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 15.0 lowest ac voltage rating at sea level **Rotor Through Connection Quantity:** 2 single section **Switch Actuator Indexing Position Quantity:** 6 single actuator **Shaft Type:** Round single actuator **Terminal Type:** Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

NSN 5930-00-548-8039

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

2.0 amperes resistive load lowest ac voltage rating at sea level

Special Features:

Two dummy terminals located on positions 6 and 12 on rear

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0