

View Online at <https://aerobasegroup.com/nsn/5930-00-548-8057>

**Thread Class:**

3b single pressure connection

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

3.844 inches

**Overall Height:**

3.250 inches

**Body Diameter:**

2.625 inches

**Body Length:**

2.750 inches

**Unthreaded Mounting Hole Diameter:**

0.196 inches

**Distance Between Mounting Facility Centers:**

3.000 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Tamper proof cap

**Thready Qty Per Inch (tpi):**

20 single pressure connection

**Contact Action Stimulus:**

Decrease

**Thread Size:**

0.438 inches single pressure connection

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

10.0 amperes resistive load first voltage

**Contact Adjustability:**

Deactuation point adjustable, preset and actuation point adjustable, preset

**Contact Adjustment Range:**

+0.50/+7.00 actuation point pounds per square inch gage and +0.50/+7.00 deactuation point pounds per square inch gage

**Contact Adjustment Type:**

Internal deactuation point screw and internal actuation point screw

**Contact Stimulus Rating:**

2.00 actuation point pounds per square inch gage and 2.00 deactuation point pounds per square inch gage

**Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

**Pressure Connector Type:**

Gasket seal, threaded internal single connection

**Media For Which Designed:**

Gas

**Style Designator:**

Cylindrical w/mounting lugs

**Thread Series Designator:**

Unf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0