

View Online at <https://aerobasegroup.com/nsn/5930-00-548-8057>

Thread Class:

3b single pressure connection

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

3.844 inches

Overall Height:

3.250 inches

Body Diameter:

2.625 inches

Body Length:

2.750 inches

Unthreaded Mounting Hole Diameter:

0.196 inches

Distance Between Mounting Facility Centers:

3.000 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Tamper proof cap

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Decrease

Thread Size:

0.438 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

10.0 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+0.50/+7.00 actuation point pounds per square inch gage and +0.50/+7.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

Internal deactuation point screw and internal actuation point screw

Contact Stimulus Rating:

2.00 actuation point pounds per square inch gage and 2.00 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Pressure Connector Type:

Gasket seal, threaded internal single connection

Media For Which Designed:

Gas

Style Designator:

Cylindrical w/mounting lugs

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0