NSN 5930-00-548-8059

Pressure Switch - Page 1 of 2

Overall Length:



View Online at https://aerobasegroup.com/nsn/5930-00-548-8059

4.125 inches
Overall Height:
3.438 inches
Body Diameter:
4.063 inches
Overall Diameter:
3.000 inches
Longest Horizontal Distance Between Mounting Centers:
0.625 inches
Longest Vertical Distance Between Mounting Centers:
3.000 inches
Pressure Switch Type:
Gage
Width Across Flats:
0.125 inches
Operating Tempurature Rating:
Between -65.0 degrees fahrenheit and 165.0 degrees fahrenheit
Mounting Method:
Bracket
Thready Qty Per Inch (tpi):
27 single pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
400.00 pounds per square inch gage

Thread Size:

0.125 inches single pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Sensing Element Burst Pressure:

750.00 pounds per square inch gage

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

1.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

27.50 actuation point pounds per square inch gage and 27.00 deactuation point pounds per square inch gage

NSN 5930-00-548-8059

Pressure Switch - Page 2 of 2

No Fiig: A048b0



Contact Voltage Rating In Volts: 30.0 dc at sea level first voltage Pressure Connector Type: Swivel nut, compression, threaded internal single connection Media For Which Designed: Gas or liquid Style Designator: Cylindrical Thread Series Designator: Npt single pressure connection Shelf Life: N/a Unit Of Measure: -- Demilitarization: