

View Online at <https://aerobasegroup.com/nsn/5930-00-548-8291>

Width Between Flats:

0.156 inches single actuator

Overall Length:

6.562 inches

Overall Height:

6.000 inches

Overall Width:

4.750 inches

First Flat Length:

0.500 inches single actuator

Shaft Diameter:

0.375 inches single actuator

Shaft Length:

1.375 inches single actuator

Unthreaded Mounting Hole Diameter:

0.406 inches single mounting facility

Individual Section Quantity:

5

Longest Horizontal Distance Between Mounting Centers:

3.750 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

5.250 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Unthreaded hole single mounting facility

Contact Voltage Rating In Volts:

500.0 ac at sea level

Shaft Flat/slot Angular Location:

45.0 degrees from contact position 1 single actuator

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, parallel flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

60.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0