## NSN 5930-00-548-8300

Rotary Switch - Page 1 of 2



Trotally Cilitati Tago Total
View Online at https://aerobasegroup.com/nsn/5930-00-548-8300
Thread Class:
2a single mounting facility
Thread Length:
0.375 inches single mounting facility
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
Between 5.375 inches and 5.437 inches
Overall Height:
1.875 inches
Overall Width:
1.625 inches
Shaft Diameter:
0.248 inches single actuator and 0.251 inches single actuator
Shaft Length:
2.000 inches single actuator
Individual Section Quantity:
4
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
2 each section rear
Throw Quantity:
4 each section rear
Mounting Method:
Threaded bushing single mounting facility
Features Provided:
Metallic inclosure
Thread Size:
0.375 inches single mounting facility
Contact Voltage Rating In Volts:
300.0 dc at sea level

**Switch Actuator Indexing Position Quantity:** 

4 single actuator

Shaft Type:

Round single actuator

**Terminal Type:** 

Tab, solder lug

**Contact Switching Action:** 

Breaks before makes each section rear

**Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

# NSN 5930-00-548-8300

Rotary Switch - Page 2 of 2



Switch Actuator	Stop	Device	Type:
-----------------	------	--------	-------

Fixed-adjustable stops single actuator

#### **Special Features:**

Shaft has two bored holes, one 0.125 in. Located o.156 in. From shaft end, other hole 0.094 in. Diameter located 0.500 in. From shaft end

#### **Style Designator:**

Circular wafer, bushing mount

### **Thread Series Designator:**

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0