# NSN 5930-00-548-8302

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-548-8302

### **Thread Class:**

2a single mounting facility

### Thread Length:

0.469 inches single mounting facility

## **Overall Length:**

4.460 inches

#### First Flat Length:

0.370 inches single actuator

#### Flat Height:

0.219 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

1.680 inches single actuator

## **Overall Diameter:**

1.870 inches

#### Individual Section Quantity:

6

### Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

1 each section front

#### Throw Quantity:

7 each section front

#### **Mounting Method:**

Threaded bushing single mounting facility

#### Thready Qty Per Inch (tpi):

32 single mounting facility

#### **Thread Size:**

0.469 inches single mounting facility

#### Contact Voltage Rating In Volts:

125.0 ac at sea level

# Switch Actuator Indexing Position Quantity:

8 single actuator

#### Shaft Type:

Round, flatted single actuator

#### **Terminal Type:**

Tab w/screw

#### **Contact Switching Action:**

Breaks before makes each section front

## Switch Actuator Positioning Increment:

45.0 degrees single actuator

# NSN 5930-00-548-8302

Rotary Switch - Page 2 of 2



Contact Load Current Rating:

3.0 amperes resistive load ac at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0