

View Online at <https://aerobasegroup.com/nsn/5930-00-548-8886>

Thread Class:

3b single pressure connection

Overall Length:

3.750 inches

Overall Height:

3.125 inches

Overall Width:

3.625 inches

Body Diameter:

3.000 inches

Unthreaded Mounting Hole Diameter:

0.203 inches

Distance Between Mounting Facility Centers:

3.000 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Thready Qty Per Inch (tpi):

20 single pressure connection

Contact Action Stimulus:

Decrease

Thread Size:

0.438 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

1.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

11.30 actuation point pounds per square inch and 13.30 deactuation point pounds per square inch and 2.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

30.0 dc at sea level second voltage

Pressure Connector Type:

Double compression, threaded internal single connection

Frequency In Hertz:

400.0 single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/mounting lugs

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0