

View Online at <https://aerobasegroup.com/nsn/5930-00-548-9040>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.375 inches single mounting facility

**Overall Length:**

2.499 inches

**First Flat Length:**

0.375 inches single actuator

**Flat Height:**

0.219 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

1.000 inches single actuator

**Overall Diameter:**

1.250 inches

**Individual Section Quantity:**

2

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

4 each section rear

**Throw Quantity:**

2 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

500.0 milliamperes resistive load ac at sea level

**Precious Material And Location:**

Contacts and rotor blade surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0