

View Online at <https://aerobasegroup.com/nsn/5930-00-548-9055>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.234 inches single mounting facility and 0.266 inches single mounting facility

**Overall Length:**

Between 3.218 inches and 3.250 inches

**Overall Height:**

Between 1.515 inches and 1.547 inches

**Overall Width:**

Between 1.296 inches and 1.328 inches

**First Flat Length:**

0.250 inches single actuator and 0.282 inches single actuator

**Flat Height:**

0.185 inches single actuator and 0.188 inches single actuator

**Shaft Diameter:**

0.248 inches single actuator and 0.251 inches single actuator

**Shaft Length:**

0.718 inches single actuator and 0.750 inches single actuator

**Nonturn Device Radius:**

0.515 inches at 3: 00 o'clock and 0.547 inches at 3: 00 o'clock

**Individual Section Quantity:**

5

**Nonturn Device Type:**

Tab at 3: 00 o'clock

**Operating Temperature Range:**

-65.0/+85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

2 each section rear

**Throw Quantity:**

5 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Shaft Flat/slot Angular Location:**

45.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:**

5 single actuator

**Shaft Type:**

Round, flatted, threaded hole single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Makes before breaks each section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Contact Load Current Rating:**

1.0 amperes resistive load dc at sea level

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0