

View Online at <https://aerobasegroup.com/nsn/5930-00-548-9055>

Thread Class:

2a single mounting facility

Thread Length:

0.234 inches single mounting facility and 0.266 inches single mounting facility

Overall Length:

Between 3.218 inches and 3.250 inches

Overall Height:

Between 1.515 inches and 1.547 inches

Overall Width:

Between 1.296 inches and 1.328 inches

First Flat Length:

0.250 inches single actuator and 0.282 inches single actuator

Flat Height:

0.185 inches single actuator and 0.188 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.251 inches single actuator

Shaft Length:

0.718 inches single actuator and 0.750 inches single actuator

Nonturn Device Radius:

0.515 inches at 3: 00 o'clock and 0.547 inches at 3: 00 o'clock

Individual Section Quantity:

5

Nonturn Device Type:

Tab at 3: 00 o'clock

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section rear

Throw Quantity:

5 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

45.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round, flatted, threaded hole single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

1.0 amperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0