NSN 5930-00-548-9260

Slide Switch - Page 1 of 1

Fiig: A053a0



View Online at https://aerobasegroup.com/nsn/5930-00-548-9260 **Body Style:** Hole mounted **Body Length:** 1.375 inches **Body Width:** Between 0.578 inches and 0.610 inches **Body Height:** Between 0.907 inches and 0.969 inches **Unthreaded Mounting Hole Diameter:** Between 0.156 inches and 0.188 inches **Actuator Height:** Between 0.188 inches and 0.234 inches **Actuator Width:** Between 0.196 inches and 0.328 inches **Actuator Position-action Relationship:** Left position maintained and right position maintained **Maximum Voltage Rating In Volts:** 115.0 ac and 30.0 dc **Mounting Method:** Unthreaded hole **Nonpile-up Contact Arrangement:** 1 pole, double throw, both positions maintained single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 20.000 amperes resistive dc and 15.000 amperes inductive dc and 7.000 amperes lamp dc and 20.000 amperes resistive ac and 15.000 amperes inductive ac and 4.000 amperes lamp ac **Terminal Type And Quantity:** 3 tab w/screw Shelf Life: N/a **Unit Of Measure: Demilitarization:** No