## NSN 5930-00-548-9316

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-548-9316

Bady Style.
Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Fungus proof and salt spray resistant
Overall Length:
3.094 inches
Overall Height:
1.641 inches
Overall Width:
0.938 inches
Body Length:
2.500 inches
Body Width:
0.766 inches
Body Height:
1.641 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.437 inches
Actuator Style:
Round
Actuator Diameter:
0.250 inches
Actuator Height:
0.750 inches
Actuator Free Position Height:
0.438 inches
Maximum Voltage Rating In Volts:
125.0 ac
Inclosure Type:
Uninclosed
Mounting Method:
Threaded hole
Thready Qty Per Inch (tpi):
32
Thread Size:
0.138 inches
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action single switch unit
Switch Release Force:
4.0 inch-ounces
Switch Actuating Force:

4.0 inch-ounces

## NSN 5930-00-548-9316

Sensitive Switch - Page 2 of 2



Δ	ctu	ato	- М	ΛV/	ama	۵ni	ŀ
н	CLU	alu	IVI	OVE	2111		L.

0.500 pretravel inches and 0.625 overtravel inches and 0.625 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:** 

25.000 amperes resistive ac

**Special Features:** 

One 0.164-32 threaded hole 0.312 in. Dp located on actuator tip parallel with length

**Thread Series Designator:** 

Unc

**Terminal Type And Quantity:** 

2 screw

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A053a0