# NSN 5930-00-548-9316

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-548-9316

Body S	Style:
--------	--------

Hole mounted

## Hazardous Locations/environmental Protection:

Fungus proof and salt spray resistant

**Overall Length:** 

3.094 inches

#### **Overall Height:**

1.641 inches

**Overall Width:** 

0.938 inches

**Body Length:** 

#### 2.500 inches

Body Width:

0.766 inches

## Body Height:

1.641 inches

## Center To Center Distance Between Mounting Facilities Parallel To Height:

0.437 inches

Actuator Style:

Round

## Actuator Diameter:

0.250 inches

## **Actuator Height:**

0.750 inches

## **Actuator Free Position Height:**

0.438 inches

#### Maximum Voltage Rating In Volts:

125.0 ac

#### Inclosure Type:

Uninclosed

#### **Mounting Method:**

Threaded hole

#### Thready Qty Per Inch (tpi):

32

#### **Thread Size:**

0.138 inches

## Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action single switch unit

## Switch Release Force:

4.0 inch-ounces

## Switch Actuating Force:

4.0 inch-ounces

# NSN 5930-00-548-9316

Sensitive Switch - Page 2 of 2



## **Actuator Movement:**

0.500 pretravel inches and 0.625 overtravel inches and 0.625 differential inches

## Contact Load Current Rating At Maximum Rated Voltage:

25.000 amperes resistive ac

## **Special Features:**

One 0.164-32 threaded hole 0.312 in. Dp located on actuator tip parallel with length

# **Thread Series Designator:**

Unc

## Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

## Unit Of Measure:

---

#### Demilitarization:

No

## Fiig:

A053a0