NSN 5930-00-548-9472



R	otary Switch - Page 1 of 2
Vie	ew Online at https://aerobasegroup.com/nsn/5930-00-548-9472
Th	nread Class:
2a	single mounting facility
Th	read Length:
0.3	375 inches single mounting facility
На	azardous Locations/environmental Protection:
Dι	ustproof
O۱	verall Length:
1.2	219 inches
Ov	verall Height:
1.5	531 inches
O۱	verall Width:
1.4	406 inches
Fir	rst Flat Length:
0.3	312 inches single actuator
Fla	at Height:
0.2	219 inches single actuator
Sh	naft Diameter:
0.2	250 inches single actuator
Sh	naft Length:
0.2	250 inches single actuator
No	onturn Device Radius:
0.3	375 inches at 10: 00 o'clock
Ind	dividual Section Quantity:
1	
No	onturn Device Type:
Ta	ab at 10: 00 o'clock
Sv	vitch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

3 single section rear

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Metallic inclosure

Thread Size:

0.375 inches single mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted single actuator

NSN 5930-00-548-9472Rotary Switch - Page 2 of 2



Terminal Type:	
Tab, solder lug	
Contact Switching Action:	
Breaks before makes single section rear	
Switch Actuator Positioning Increment:	
30.0 degrees single actuator	
Switch Actuator Stop Device Type:	
Fixed stop single actuator	
Special Features:	
Dummy terminals located at positions 1 6 9 rear	
Precious Material And Location:	
Contact surfaces silver	
Precious Material:	
Silver	
Style Designator:	
Circular wafer, bushing mount	
Thread Series Designator:	
Unef single mounting facility	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A052b0	