

| NSN 5930-00-548-9488 Rotary Switch - Page 1 of 2 | AeroBas Grou |
|---|-----------------|
| View Online at https://aerobasegroup.com/nsn/5930-00-548-9488 | |
| Thread Length: | |
| 0.468 inches single mounting facility | |
| Hazardous Locations/environmental Protection: | |
| Dustproof and explosion proof | |
| Overall Length: | |
| 2.250 inches | |
| Overall Height: | |
| 1.875 inches | |
| Overall Width | |

First Flat Length:

0.390 inches single actuator

Flat Height:

1.625 inches

0.187 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.500 inches single actuator

Individual Section Quantity:

Knob Manufacturer Code:

81349

Knob Manufacturer Part Number:

An3220-3

Nonturn Device Type:

Slotted bushing at 12: 00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Pole Quantity:

1 single section front

Throw Quantity:

7 single section front

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.469 inches single mounting facility

Shaft Flat/slot Angular Location:

90.0 degrees from nonturn device single actuator

NSN 5930-00-548-9488Rotary Switch - Page 2 of 2



| Switch Actuator Indexing Position Quantity: |
|---|
| 8 single actuator |
| Shaft Type: |
| Round, flatted single actuator |
| Terminal Type: |
| Tab w/screw |
| Contact Switching Action: |
| Breaks before makes single section front |
| Switch Actuator Positioning Increment: |
| 45.0 degrees single actuator |
| Switch Actuator Stop Device Type: |
| Fixed stop single actuator |
| Style Designator: |
| Circular wafer, bushing mount |
| Thread Series Designator: |
| Uns single mounting facility |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A052b0 |