

View Online at <https://aerobasegroup.com/nsn/5930-00-548-9793>

**Hazardous Locations/environmental Protection:**

Moisture proof

**First Flat Length:**

0.734 inches single actuator

**Shaft Diameter:**

0.800 inches single actuator

**Shaft Length:**

1.360 inches single actuator

**Unthreaded Mounting Hole Diameter:**

0.213 inches single mounting facility

**Individual Section Quantity:**

6

**Longest Horizontal Distance Between Mounting Centers:**

2.298 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.298 inches single mounting facility

**Switch Contact Basic Design:**

Pile-up

**Mounting Method:**

Unthreaded hole single mounting facility

**Features Provided:**

Metallic inclosure

**Contact Voltage Rating In Volts:**

125.0 ac at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round, square, threaded hole single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Makes before breaks, breaks before makes each section front

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

10.0 amperes resistive load ac at sea level

**Style Designator:**

Tap, circuit selector

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0