

View Online at <https://aerobasegroup.com/nsn/5930-00-548-9793>

Hazardous Locations/environmental Protection:

Moisture proof

First Flat Length:

0.734 inches single actuator

Shaft Diameter:

0.800 inches single actuator

Shaft Length:

1.360 inches single actuator

Unthreaded Mounting Hole Diameter:

0.213 inches single mounting facility

Individual Section Quantity:

6

Longest Horizontal Distance Between Mounting Centers:

2.298 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.298 inches single mounting facility

Switch Contact Basic Design:

Pile-up

Mounting Method:

Unthreaded hole single mounting facility

Features Provided:

Metallic inclosure

Contact Voltage Rating In Volts:

125.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, square, threaded hole single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Makes before breaks, breaks before makes each section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0