

View Online at <https://aerobasegroup.com/nsn/5930-00-548-9878>

Thread Class:

2a single mounting facility

Thread Length:

0.469 inches single mounting facility

Overall Length:

2.938 inches

First Flat Length:

0.469 inches single actuator

Flat Height:

0.188 inches single actuator

Shaft Diameter:

0.248 inches single actuator

Shaft Length:

1.000 inches single actuator

Overall Diameter:

2.188 inches

Individual Section Quantity:

4

Nonturn Device Type:

Slotted bushing at 12: 00 o'clock

Operating Temperature Range:

-20.0/+65.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.469 inches single mounting facility

Contact Voltage Rating In Volts:

24.0 dc at sea level

Shaft Flat/slot Angular Location:

315.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load dc at sea level and 2.0 amperes lamp load dc at sea level

Style Designator:

Tap, circular, bushing mount

Test Data Document:

82260-2011414 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0