## NSN 5930-00-548-9879

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-548-9879

Th	rea	d (	CI	ass:	

2b single mounting facility

**Hazardous Locations/environmental Protection:** 

Dustproof

**Overall Length:** 

3.125 inches

**Overall Height:** 

2.500 inches

**Overall Width:** 

2.500 inches

First Flat Length:

0.500 inches single actuator

Flat Height:

0.216 inches single actuator

**Shaft Diameter:** 

0.248 inches single actuator and 0.251 inches single actuator

**Shaft Length:** 

0.875 inches single actuator

**Individual Section Quantity:** 

5

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

1 each section front

**Throw Quantity:** 

2 each section front

**Mounting Facility Circle Radius:** 

1.156 inches single mounting facility

**Mounting Method:** 

Threaded hole single mounting facility

Thready Qty Per Inch (tpi):

24 single mounting facility

**Thread Size:** 

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

120.0 dc at sea level

**Shaft Flat/slot Angular Location:** 

270.0 degrees from contact position 1 single actuator

**Mounting Facility Pattern:** 

Four position circular single mounting facility

**Switch Actuator Indexing Position Quantity:** 

2 single actuator

## **NSN 5930-00-548-9879**Rotary Switch - Page 2 of 2



Shaft Type:
Round, flatted single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section front
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
10.0 amperes resistive load dc at sea level
Style Designator:
Tap, circuit selector
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A052b0