

View Online at <https://aerobasegroup.com/nsn/5930-00-549-0100>

Hazardous Locations/environmental Protection:

Watertight

Overall Height:

4.875 inches

Overall Width:

4.375 inches

First Flat Length:

0.718 inches single actuator

Flat Height:

0.067 inches single actuator

Shaft Diameter:

0.375 inches single actuator

Shaft Length:

0.500 inches single actuator

Unthreaded Mounting Hole Diameter:

0.406 inches single mounting facility

Individual Section Quantity:

1

Knob Manufacturer Code:

15605

Knob Manufacturer Part Number:

53-527-3

Longest Horizontal Distance Between Mounting Centers:

4.875 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

3.500 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section front

Throw Quantity:

2 single section front

Mounting Method:

Base single mounting facility

Features Provided:

Actuator knob

Contact Voltage Rating In Volts:

500.0 ac at sea level

Switch Actuator Momentary Position:

Clockwise single actuator and counterclockwise single actuator

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes single section front

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Contact Load Current Rating:

15.0 amperes resistive load ac at sea level

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0