NSN 5930-00-549-0100

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-549-0100

Hazardous Locations/environmental Protection:
Watertight
Overall Height:
4.875 inches
Overall Width:
4.375 inches
First Flat Length:
0.718 inches single actuator
Flat Height:
0.067 inches single actuator
Shaft Diameter:
0.375 inches single actuator
Shaft Length:
0.500 inches single actuator
Unthreaded Mounting Hole Diameter:
0.406 inches single mounting facility
Individual Section Quantity:
1
Knob Manufacturer Code:
15605
Knob Manufacturer Part Number:
53-527-3
Longest Horizontal Distance Between Mounting Centers:
4.875 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
3.500 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
2 single section front
Throw Quantity:
2 single section front
Mounting Method:
Base single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
500.0 ac at sea level
Switch Actuator Momentary Position:
Clockwise single actuator and counterclockwise single actuator

Mounting Facility Pattern:

Four position rectangular single mounting facility

NSN 5930-00-549-0100

Rotary Switch - Page 2 of 2



Switch Actuator Indexing Position Quantity: 3 single actuator **Shaft Type:** Round, flatted single actuator **Terminal Type:** Tab w/screw **Contact Switching Action:** Breaks before makes single section front **Switch Actuator Positioning Increment:** 36.0 degrees single actuator **Contact Load Current Rating:** 15.0 amperes resistive load ac at sea level Shelf Life: N/a **Unit Of Measure:** Demilitarization:

No Fiig: A052b0