NSN 5930-00-549-0206

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-549-0206

| Body Style: | | |
|------------------------------------------------------------------------------------|--|--|
| Hole mount | | |
| Hazardous Locations/environmental Protection: | | |
| Oil resistant | | |
| Overall Length: | | |
| 1.937 inches | | |
| Center To Center Distance Between Mounting Facilities Parallel To Length: | | |
| 1.500 inches | | |
| Overall Height: | | |
| 1.844 inches | | |
| Overall Width: | | |
| 1.437 inches | | |
| Body Length: | | |
| 1.375 inches | | |
| Body Width: | | |
| 1.437 inches | | |
| Body Height: | | |
| 1.469 inches | | |
| Case Material: | | |
| Plastic | | |
| Actuator Diameter: | | |
| 0.937 inches | | |
| Actuator Height: | | |
| 0.375 inches | | |
| Actuator Color: | | |
| Red single actuator | | |
| Maximum Voltage Rating In Volts: | | |
| 600.0 ac and 600.0 dc | | |
| Inclosure Type: | | |
| Fully enclosed | | |
| Thready Qty Per Inch (tpi): | | |
| 32 | | |
| Thread Size: | | |
| 0.164 inches | | |
| Nonpile-up Contact Arrangement: | | |
| 1 two circuit, double break/double make, one position momentary single switch unit | | |
| Contact Load Current Rating At Maximum Rated Voltage: | | |
| 0.200 amperes inductive dc and 6.000 amperes resistive ac | | |
| Thread Series Designator: | | |
| Unc | | |
| Terminal Type And Quantity: | | |
| 4 tab w/screw | | |

NSN 5930-00-549-0206

Push Switch - Page 2 of 2



| | Life: |
|--|-------|
| | |
| | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0