

View Online at <https://aerobasegroup.com/nsn/5930-00-549-0246>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.250 inches single mounting facility

**Overall Length:**

4.438 inches

**Overall Height:**

1.875 inches

**Overall Width:**

1.625 inches

**First Flat Length:**

0.438 inches single actuator

**Flat Height:**

0.219 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.750 inches single actuator

**Nonturn Device Radius:**

0.165 inches at 10: 00 o'clock

**Individual Section Quantity:**

6

**Nonturn Device Type:**

Tab at 10: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical and nonpile-up nonsymmetrical

**Pole Quantity:**

2 4th section front

**Throw Quantity:**

6 3rd section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Shaft Flat/slot Angular Location:**

285.0 degrees from contact position 1 single actuator

**Rotor Through Connection Quantity:**

2 3rd section

**Switch Actuator Indexing Position Quantity:**

6 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes 2nd section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop-breakoff tab single actuator

**Contact Load Current Rating:**

1.0 amperes resistive load dc at sea level

**Special Features:**

Sect 5 rear and sect 6 front 12 dummy terminals ea

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0