NSN 5930-00-549-0290

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-549-0290

Hazardous Locations/environmental Protection:
Watertight
Overall Height:
2.688 inches
Overall Width:
4.500 inches
Shaft Diameter:
0.436 inches single actuator
Shaft Length:
1.375 inches single actuator
Unthreaded Mounting Hole Diameter:
0.344 inches single mounting facility
Individual Section Quantity:
1
Longest Horizontal Distance Between Mounting Centers:
7.750 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
3.750 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 single section front
Throw Quantity:
2 single section front
Features Provided:
Metallic inclosure
Contact Voltage Rating In Volts:
120.0 dc at sea level
Mounting Facility Pattern:
Two position diagonal single mounting facility
Two position diagonal single mounting facility Switch Actuator Indexing Position Quantity:
Switch Actuator Indexing Position Quantity:
Switch Actuator Indexing Position Quantity: 3 single actuator
Switch Actuator Indexing Position Quantity: 3 single actuator Shaft Type:
Switch Actuator Indexing Position Quantity: 3 single actuator Shaft Type: Round single actuator
Switch Actuator Indexing Position Quantity: 3 single actuator Shaft Type: Round single actuator Terminal Type:
Switch Actuator Indexing Position Quantity: 3 single actuator Shaft Type: Round single actuator Terminal Type: Tab w/screw
Switch Actuator Indexing Position Quantity: 3 single actuator Shaft Type: Round single actuator Terminal Type: Tab w/screw Contact Switching Action:

Contact Load Current Rating:

6.0 amperes resistive load dc at sea level

NSN 5930-00-549-0290

Rotary Switch - Page 2 of 2



Special	Features:
---------	-----------

Marked limit and indicating switch

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0