## NSN 5930-00-549-0491

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-549-0491

**Thread Class:** 

2a single mounting facility

**Thread Length:** 

0.500 inches single mounting facility

**Overall Length:** 

4.812 inches

**Shaft Length:** 

0.625 inches single actuator

**Overall Diameter:** 

2.812 inches

**Individual Section Quantity:** 

6

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

2 each section front

**Throw Quantity:** 

4 each section front

**Mounting Facility Circle Radius:** 

0.906 inches single mounting facility

**Mounting Method:** 

Threaded stud single mounting facility

**Thread Size:** 

0.190 inches single mounting facility

**Contact Voltage Rating In Volts:** 

125.0 ac at sea level

**Mounting Facility Pattern:** 

Four position circular single mounting facility

**Switch Actuator Indexing Position Quantity:** 

4 single actuator

**Shaft Type:** 

Rectangular/square, threaded hole single actuator

**Square Shaft Size:** 

0.250 inches single actuator

**Terminal Type:** 

Screw

**Contact Switching Action:** 

Breaks before makes each section front

**Switch Actuator Positioning Increment:** 

45.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Adjustable stop single actuator

## NSN 5930-00-549-0491

Rotary Switch - Page 2 of 2



| Contact Load | Current | Rating: |
|--------------|---------|---------|
|--------------|---------|---------|

10.0 amperes resistive load ac at sea level

**Precious Material And Location:** 

Contact surfaces silver

**Precious Material:** 

Silver

Style Designator:

Tap, circular frame

**Thread Series Designator:** 

Unf single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A052b0