NSN 5930-00-549-0601

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-549-0601

view Orillite at https://aerobasegroup.com/nsn/3930-00-349-0001
Body Style:
Hole mounted
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 0.872 inches and 0.878 inches
Body Length:
Between 1.079 inches and 1.109 inches
Body Width:
Between 0.385 inches and 0.415 inches
Body Height:
Between 0.610 inches and 0.650 inches
Unthreaded Mounting Hole Diameter:
Between 0.113 inches and 0.116 inches
Actuator Length:
Between 0.105 inches and 0.115 inches
Actuator Style:
Rectangular
Actuator Width:
Between 0.160 inches and 0.170 inches
Actuator Free Position Height:
0.625 inches
Actuator Adapter Style:
Roller leaf
Maximum Voltage Rating In Volts:
250.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:
Between 6.0 ounces and 14.0 ounces
Contact Load Current Rating At Maximum Rated Voltage:
250.000 milliamperes resistive dc and 5.000 amperes resistive ac
Terminal Type And Quantity:
2 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5930-00-549-0601

Sensitive Switch - Page 2 of 2



Fiig:

A053a0