## NSN 5930-00-549-0601

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-549-0601

## Body Style:

Hole mounted

## Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.872 inches and 0.878 inches

## **Body Length:**

Between 1.079 inches and 1.109 inches

#### **Body Width:**

Between 0.385 inches and 0.415 inches

#### **Body Height:**

Between 0.610 inches and 0.650 inches

#### **Unthreaded Mounting Hole Diameter:**

Between 0.113 inches and 0.116 inches

#### Actuator Length:

Between 0.105 inches and 0.115 inches

#### Actuator Style:

Rectangular

#### Actuator Width:

Between 0.160 inches and 0.170 inches

#### **Actuator Free Position Height:**

0.625 inches

## Actuator Adapter Style:

Roller leaf

#### Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

## Inclosure Type:

Fully enclosed

#### Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action single switch unit

#### Switch Release Force:

4.0 ounces

#### Switch Actuating Force:

Between 6.0 ounces and 14.0 ounces

#### Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 5.000 amperes resistive ac

#### **Terminal Type And Quantity:**

2 screw

Shelf Life:

N/a

## Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5930-00-549-0601

Sensitive Switch - Page 2 of 2

Fiig: A053a0

