## NSN 5930-00-549-0720

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-549-0720

#### **Body Style:**

Hole mounted

Hazardous Locations/environmental Protection:

Weatherproof

Switch Actuator Quantity:

7

## Housing Width:

1.969 inches

## Center To Center Distance Between Housing Mounting Facilities Parallel To Height:

1.812 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.750 inches

Maximum Voltage Rating In Volts:

600.0 ac and 250.0 dc

#### Inclosure Type:

Fully enclosed

## Mounting Method:

Threaded hole

#### Features Provided:

Actuator seal

#### Thread Size:

0.190 inches

#### Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

#### Switch Release Force:

12.0 ounces

#### Switch Actuating Force:

48.0 ounces

#### **Actuator Movement:**

Between 0.078 pretravel inches and 0.188 overtravel inches and 0.004 differential inches

#### Contact Load Current Rating At Maximum Rated Voltage:

700.000 milliamperes resistive dc and 2.000 amperes resistive ac

#### **Thread Series Designator:**

Unf

#### **Terminal Type And Quantity:**

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5930-00-549-0720

Sensitive Switch - Page 2 of 2

**Fiig:** A053a0

