NSN 5930-00-549-0720



Sensitive Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-549-0720 **Body Style:** Hole mounted **Hazardous Locations/environmental Protection:** Weatherproof **Switch Actuator Quantity: Housing Width:** 1.969 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Height: 1.812 inches **Center To Center Distance Between Housing Mounting Facilities Parallel To Length:** 2.750 inches **Maximum Voltage Rating In Volts:** 600.0 ac and 250.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded hole **Features Provided:** Actuator seal **Thread Size:** 0.190 inches **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary single switch unit **Switch Release Force:** 12.0 ounces **Switch Actuating Force:** 48.0 ounces **Actuator Movement:** Between 0.078 pretravel inches and 0.188 overtravel inches and 0.004 differential inches **Contact Load Current Rating At Maximum Rated Voltage:** 700.000 milliamperes resistive dc and 2.000 amperes resistive ac **Thread Series Designator:** Unf **Terminal Type And Quantity:** 3 screw Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5930-00-549-0720

Sensitive Switch - Page 2 of 2



Fiig:

A053a0