NSN 5930-00-549-0732

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-549-0732

Body Style:

Hole mounted

Overall Length:

Between 1.922 inches and 1.954 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.998 inches and 1.002 inches

Overall Width:

Between 0.672 inches and 0.694 inches

Body Length:

Between 1.922 inches and 1.954 inches

Body Width:

Between 0.672 inches and 0.694 inches

Body Height:

Between 1.031 inches and 1.063 inches

Unthreaded Mounting Hole Diameter:

Between 0.138 inches and 0.142 inches

Actuator Length:

Between 0.140 inches and 0.172 inches

Actuator Style:

Roller arm

Actuator Roller Diameter:

Between 0.359 inches and 0.391 inches

Maximum Voltage Rating In Volts:

125.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded hole

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Actuating Force:

1.5 ounces

Actuator Movement:

0.062 overtravel inches and 0.030 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive ac

Thread Series Designator:

Unc

NSN 5930-00-549-0732 Sensitive Switch - Page 2 of 2



rerminal Type And Quantity:
3 screw
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No

Fiig: A053a0