NSN 5930-00-549-0749

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-549-0749 **Body Style:** Hole mounted **Case Material:** Metal **Housing Height:** 1.750 inches **Housing Length:** 1.205 inches **Housing Width:** 1.000 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Length: 1.000 inches **Maximum Voltage Rating In Volts:** 250.0 ac and 250.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded hole Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.469 inches **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary single switch unit **Switch Release Force:** 4.0 ounces **Switch Actuating Force:** 28.0 ounces **Actuator Movement:** Between 0.030 pretravel inches and 0.140 overtravel inches and 0.005 differential inches **Contact Load Current Rating At Maximum Rated Voltage:** 250.000 milliamperes resistive dc and 15.000 amperes resistive ac **Thread Series Designator:** Uns **Terminal Type And Quantity:** 3 screw Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5930-00-549-0749 Sensitive Switch - Page 2 of 2



Fiig:

A053a0