## NSN 5930-00-549-1917

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-549-1917

| Body Style:  |
|--|
| Panel mounted  |
| Hazardous Locations/environmental Protection:                      |
| Explosion proof and humidity resistant                             |
| Overall Length:  |
| 3.706 inches   |
| Overall Height:  |
| 0.750 inches   |
| Overall Width:   |
| 0.750 inches   |
| Body Width:  |
| 0.750 inches   |
| Body Height:   |
| 0.750 inches   |
| Case Material:   |
| Metal  |
| Actuator Length:   |
| 0.620 inches   |
| Actuator Style:  |
| Rectangular  |
| Actuator Height:   |
| 0.100 inches   |
| Actuator Width:  |
| 0.620 inches   |
| Actuator Color:  |
| White single actuator  |
| Illuminated Actuator Color:  |
| White single actuator  |
| Actuator Inscription:  |
| Adi single actuator  |
| Maximum Voltage Rating In Volts:                                   |
| 115.0 ac and 28.0 dc   |
| Mounting Surface To Terminal End Distance:                         |
| 3.560 inches   |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Method:   |
| Panel  |
| Features Provided:   |
| Full display lens and holding solenoid                             |
| Nonpile-up Contact Arrangement:                                    |
| 4 pole, double throw, both positions maintained single switch unit |

## NSN 5930-00-549-1917

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac

**Precious Material And Location:** 

Contacts silver

**Terminal Type And Quantity:** 

1 socket, integrated wire termination

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A053a0