

View Online at <https://aerobasegroup.com/nsn/5930-00-550-1325>

Thread Class:

2a

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Body Length:

2.812 inches

Body Width:

0.780 inches

Body Height:

1.369 inches

Case Material:

Metal

Switch Actuator Quantity:

1

Actuator Style:

Roller arm

Actuator Free Position Height:

1.812 inches

Actuator Roller Diameter:

0.370 inches

Actuator Roller Width:

0.157 inches

Actuator Adapter Style:

Roller arm

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

2.0 ounces

Switch Actuating Force:

28.0 ounces

Actuator Movement:

Between 0.242 pretravel inches and 0.250 overtravel inches and 0.050 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac and 3.000 amperes motor ac

Thread Series Designator:

Unc

Terminal Type And Quantity:

3 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0