

View Online at <https://aerobasegroup.com/nsn/5930-00-550-1325>

**Thread Class:**

2a

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.000 inches

**Body Length:**

2.812 inches

**Body Width:**

0.780 inches

**Body Height:**

1.369 inches

**Case Material:**

Metal

**Switch Actuator Quantity:**

1

**Actuator Style:**

Roller arm

**Actuator Free Position Height:**

1.812 inches

**Actuator Roller Diameter:**

0.370 inches

**Actuator Roller Width:**

0.157 inches

**Actuator Adapter Style:**

Roller arm

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.138 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

2.0 ounces

**Switch Actuating Force:**

28.0 ounces

**Actuator Movement:**

Between 0.242 pretravel inches and 0.250 overtravel inches and 0.050 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac and 3.000 amperes motor ac

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

3 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0