

View Online at <https://aerobasegroup.com/nsn/5930-00-550-9055>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.579 inches

Overall Height:

0.750 inches

Overall Width:

0.750 inches

Body Diameter:

0.562 inches

Bushing Length:

0.378 inches

Case Material:

Metal

Actuator Length:

0.750 inches

Actuator Style:

Rectangular

Actuator Height:

0.410 inches

Actuator Width:

0.380 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Maximum Voltage Rating In Volts:

28.0 dc

Mounting Surface To Terminal End Distance:

0.701 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0