

View Online at <https://aerobasegroup.com/nsn/5930-00-552-0161>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

3.660 inches

**Actuator Length:**

1.560 inches

**Actuator Style:**

Roller arm

**Actuator Roller Diameter:**

0.750 inches

**Actuator Roller Width:**

0.312 inches

**Housing Height:**

2.560 inches

**Housing Length:**

3.660 inches

**Housing Width:**

2.060 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Height:**

1.812 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

2.750 inches

**Maximum Voltage Rating In Volts:**

480.0 ac and 250.0 dc

**End Application:**

Forrestal class cv, blue ridge class lcc-19, nimitz class cvn, emory s. Land class as, wasp class lhd, deck machinery, usns stalwart class tagos, tarawa class lha, supply class aoe.

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

4.0 ounces

**Criticality Code Justification:**

Feat

**Switch Actuating Force:**

8.0 ounces

**Actuator Movement:**

0.007 differential inches and 0.219 pretravel inches

**Contact Load Current Rating At Maximum Rated Voltage:**

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0