

View Online at <https://aerobasegroup.com/nsn/5930-00-552-0161>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

3.660 inches

Actuator Length:

1.560 inches

Actuator Style:

Roller arm

Actuator Roller Diameter:

0.750 inches

Actuator Roller Width:

0.312 inches

Housing Height:

2.560 inches

Housing Length:

3.660 inches

Housing Width:

2.060 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Height:

1.812 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.750 inches

Maximum Voltage Rating In Volts:

480.0 ac and 250.0 dc

End Application:

Forrestal class cv, blue ridge class lcc-19, nimitz class cvn, emory s. Land class as, wasp class lhd, deck machinery, usns stalwart class tagos, tarawa class lha, supply class aoe.

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Criticality Code Justification:

Feat

Switch Actuating Force:

8.0 ounces

Actuator Movement:

0.007 differential inches and 0.219 pretravel inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Special Features:

Weapon system essential

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0