# NSN 5930-00-552-1199

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-552-1199

## Body Style:

Hole mounted

#### **Overall Length:**

0.781 inches

### Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

#### **Overall Width:**

0.250 inches

#### **Body Length:**

0.781 inches

#### **Body Width:**

0.250 inches

#### **Body Height:**

0.356 inches

#### **Case Material:**

Plastic

# Unthreaded Mounting Hole Diameter:

0.088 inches

#### Actuator Style:

Round

#### Actuator Diameter:

0.092 inches

#### **Actuator Free Position Height:**

0.330 inches

#### Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

#### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Unthreaded hole

#### Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

#### Switch Release Force:

1.0 ounces

#### Switch Actuating Force:

5.0 ounces

#### **Actuator Movement:**

Between 0.030 pretravel inches and 0.005 overtravel inches and 0.004 differential inches

# Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

## **Precious Material And Location:**

Contacts silver

# NSN 5930-00-552-1199

Sensitive Switch - Page 2 of 2



## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0