NSN 5930-00-552-1679

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-552-1679
Thread Class:
2b single mounting facility
Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
4.125 inches
Overall Height:
2.531 inches
Overall Width:
2.531 inches
First Flat Length:
0.875 inches single actuator
Shaft Diameter:
0.375 inches single actuator
Shaft Length:
1.125 inches single actuator
Individual Section Quantity:
4
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
8164-12y
Knob Specificationial Markings:
Arrow sign
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Mounting Facility Circle Radius:
3.875 inches single mounting facility
Mounting Method:
Bracket single mounting facility and threaded hole single mounting facility
Features Provided:
Actuator knob
Thready Qty Per Inch (tpi):
20 single mounting facility
Thread Size:
0.250 inches single mounting facility
Contact Voltage Rating In Volts:
500.0 ac at sea level
Mounting Facility Pottorns

Mounting Facility Pattern:

Four position circular single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

NSN 5930-00-552-1679Rotary Switch - Page 2 of 2



Shaft Type:
Round, parallel flatted, threaded hole single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Contact Load Current Rating:
30.0 amperes resistive load ac at sea level
Style Designator:
Tap, circuit selector
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A052b0