

View Online at <https://aerobasegroup.com/nsn/5930-00-552-1682>

**Thread Class:**

2b single mounting facility

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

3.563 inches

**Overall Height:**

2.812 inches

**Overall Width:**

2.812 inches

**First Flat Length:**

0.438 inches single actuator

**Shaft Diameter:**

0.281 inches single actuator

**Shaft Length:**

0.875 inches single actuator

**Individual Section Quantity:**

4

**Knob Manufacturer Code:**

82121

**Knob Manufacturer Part Number:**

B

**Longest Horizontal Distance Between Mounting Centers:**

2.297 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.297 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section periphery

**Throw Quantity:**

3 each section periphery

**Mounting Method:**

Bracket single mounting facility and threaded hole single mounting facility

**Features Provided:**

Actuator knob

**Thready Qty Per Inch (tpi):**

24 single mounting facility

**Thread Size:**

0.190 inches single mounting facility

**Contact Voltage Rating In Volts:**

125.0 dc at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Shaft Type:**

Round, square single actuator

**Square Shaft Size:**

0.250 inches single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes each section periphery

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Adjustable stop single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load dc at sea level

**Style Designator:**

Tap, circuit selector

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0