NSN 5930-00-552-1934

Sensitive Switch - Page 1 of 2

Body Style:Hole mounted



View Online at https://aerobasegroup.com/nsn/5930-00-552-1934

Center To Center Distance Between Mounting Facilities Parallel To Length:

| 2.188 inches |
|--|
| Body Length: |
| 2.690 inches |
| Body Width: |
| 1.220 inches |
| Body Height: |
| 1.287 inches |
| Case Material: |
| Metal |
| Unthreaded Mounting Hole Diameter: |
| 0.171 inches |
| Actuator Length: |
| 1.570 inches |
| Actuator Style: |
| Roller arm |
| Actuator Free Position Height: |
| 1.480 inches |
| Actuator Roller Diameter: |
| 0.750 inches |
| Actuator Roller Width: |
| 0.312 inches |
| Maximum Voltage Rating In Volts: |
| 480.0 ac |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Unthreaded hole |
| Nonpile-up Contact Arrangement: |
| 2 pole, double throw, both positions maintained single switch unit |
| Switch Release Force: |
| 8.0 ounces |
| Switch Actuating Force: |
| 40.0 ounces |
| Actuator Movement: |
| Between 0.188 pretravel inches and 0.219 overtravel inches and 0.094 differential inches |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 15.000 amperes resistive ac |
| Terminal Type And Quantity: |
| 6 screw |

NSN 5930-00-552-1934

Sensitive Switch - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0