

View Online at <https://aerobasegroup.com/nsn/5930-00-552-8935>

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Overall Length:

5.281 inches

Overall Height:

2.312 inches

Overall Width:

1.750 inches

First Flat Length:

0.375 inches single actuator

Flat Height:

0.219 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.250 inches single actuator

Individual Section Quantity:

5

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

6 4th section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

24 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks each section rear

Switch Actuator Positioning Increment:

15.0 degrees single actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Special Features:

2 dummy terminal front 1 dummy terminal rear section 1, 2 dummy terminals front and rear section 2, 4 dummy terminals front 1 on rear section 3, 1 dummy terminal front 5 rear section 4, 2 dummy terminals front and rear section 5

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0